



ELECTRONIC TUBE REFERENCE

ITL101

Power - Triode (over 1000V 100W) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TRIODE

Power transmitting triode intended for RF amplification, oscillation, or related professional service. Manufacturer documentation emphasizes radio-frequency operation, substantial plate loading, and transmitter or industrial applications.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	— / —	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Triode	
MAXIMUM PLATE VOLTAGE	8000 V
MAXIMUM PLATE DISSIPATION	10000 W
MAXIMUM CATHODE CURRENT	4 A
Published ratings and characteristics promoted where reliably recoverable from the approved sheet.	

Air-cooled industrial power triode.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1969 Brown Boveri

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1969 BROWN BOVERI

Section 1 · Triode

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum Frequency	120 MHz	—
RF/Output Power	22000 W	Quick Reference, stated operating class where applicable