



ELECTRONIC TUBE REFERENCE

K67A1

Specialized - Klystron electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

KLYSTRON

Russian reflex klystron microwave oscillator, nominal frequency 66700 MHz and RF output 5 mW.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 1 A	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 0 Klystron

No fixed ratings recorded.

Reflex klystron; Cathode Type: Oxide, Indirect Heating; Envelope: metal, 3.6x1.8mm waveguide output, slow mechanical tuning; Mass: 300g; Cooling Method: Forced Air; Frequency Band: 66700MHz; Frequency Band Minimum: 63735MHz; Frequency Band Maximum: 69665MHz; Output Power: 5mW; Tuning Transconductance, Mhz/Ma: 16; Filament Voltage, V: 6.3; Filament Current, A: 1; Resonator Voltage, V: 2400; Reflector Negative Voltage, V: 225; Reflector Negative Voltage, V Minimum: 50; Reflector Negative Voltage, V Maximum: 400

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker