ELECTRONIC TUBE REFERENCE

K98G

Specialized - Klystron electronic tube

CONSOLIDATED TECHNICAL DATA
1 SECTION
CONSTRUCTION
KLYSTRON

Russian reflex klystron, frequency band 1.6cm, output power 180mW.

General characteristics

BASE DESIGNATION	–	**BASE PINS**	–
NOMINAL HEATER	6.3 V / 1 A	**PARALLEL HEATER**	– / –
HEATING	Indirect	**SERIES OPERATION**	Not specified
CATHODE ARRANGEMENT	Separate cathodes	**SECTION CONSTRUCTION**	Similar

Section ratings

SECTION0 Klystron

No fixed ratings recorded.

Reflex klystron; Cathode Type: Oxide, Indirect Heating: Envelope: metal-ceramic,11x5.5mm waveguide output, slow mechanical tuning: Mass: 240g: Cooling Method: Forced Air: Frequency Band: 1.6cm: Frequency Band Minimum: 1.53cm: Frequency Band Maximum: 1.6cm: Output Power: 180mW: Tuning Transconductance, Mhz/Ma: 1: Tuning Range, Mhz: 16: Filament Voltage, V: 6.3: Filament Current, A: 1: Resonator Voltage, V: 1500: Reflector Negative Voltage, V: 320: Reflector Negative Voltage, V Minimum: 120: Reflector Negative Voltage, V Maximum: 520

Tube Tinker

An independent reference for electronic tubes, vacuum tubes, and their source documents.

Catalog Tube types Full books Blog Feedback & corrections

© 2026 Tube Tinker