

ELECTRONIC TUBE REFERENCE

KU274

Specialized - Thyatron electronic tube

CONSOLIDATED TECHNICAL DATA
1 SECTION
CONSTRUCTION
THYRATRON

Large ceramic hydrogen thyatron rated for approximately 60 MW pulse switching.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / —	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Thyatron	
MAXIMUM PLATE VOLTAGE	50000 V
MAXIMUM CATHODE CURRENT	2400 A

Large ceramic hydrogen thyatron rated for 60-MW pulse service.

SOURCE OPERATING CONDITIONS

1962 ITT

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1962 ITT

Section 1 · Thyatron

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater Voltage	6.3 V	—
Heater Current	25-35 A	—
Minimum Heating Time	600 s	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum Peak Anode Voltage Forward	50000 V	—
Maximum Peak Anode Voltage Inverse	50000 V	—
Maximum Peak Anode Current	2400 A	—
Maximum Average Anode Current	4 A	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker