



ELECTRONIC TUBE REFERENCE

L410

Voltage - Triode (single high frequency) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TRIODE

Low-frequency amplifying triode intended primarily for transformer coupling, also usable as a detector following one or more high-frequency stages.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	4 V / 100 mA	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Triode	
PLATE RESISTANCE	8900 Ω
TRANSCONDUCTANCE	0.00175 S
AMPLIFICATION FACTOR	15
MAXIMUM PLATE VOLTAGE	150 V
<i>Promoted values mapped from printed rating/approximate-data tables; additional operating points and capacitances retained as parameters.</i>	

Primarily a low-frequency amplifying valve for transformer coupling; may also be employed as a detector after one or more H.F. stages.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

192X Marconi Valve

Published test conditions and operating points. Values on this page are preserved as reported by this source.

192X MARCONI VALVE

Section 1 · Triode

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Published operating data	See source	Operating curves/table are present on the approved one-page source; values not promoted unless unambiguous in searchable text.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1955 Marconi

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1955 MARCONI

Section 1 · Triode

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Typical Anode Voltage	100 V	—
Typical Grid Bias	-1.5 V	—