



ELECTRONIC TUBE REFERENCE

LC511

Nixie electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

NIXIE

Cold-cathode numeric or character indicator cross-referenced to RFT Z560M. The comparison catalog provides striking, maintaining, extinction, current, and display data for the RFT type but cautions that comparable tubes are not necessarily electrically identical.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	— / —	PARALLEL HEATER	— / —
HEATING	Indirect; cold cathode	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Nixie	
MAXIMUM CATHODE CURRENT	2.5 mA
MINIMUM REGULATOR CURRENT	1 A
MAXIMUM REGULATOR CURRENT	2.5 A
STARTING VOLTAGE	145 V
MAINTAINING VOLTAGE	135 V
<i>Cold-cathode display section; promoted starting/maintaining voltages and current range are published for comparable RFT type Z560M.</i>	

LC511 is a cold-cathode numeric or character indicator tube listed in the supplied German comparison catalog as comparable to RFT type Z560M. The catalog publishes 145 V anode striking, 135 V maintaining, 120 V extinction, a 1–2.5 mA cathode-current range, and associated display and mechanical data for that RFT type. The source explicitly cautions that comparable tubes are not necessarily identical, so these mapped RFT values are retained as comparison data rather than asserted as exact original-manufacturer ratings.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1971 Nixie RFT

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1971 NIXIE RFT

Section 1 · Nixie

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Comparable RFT Type	Z560M	Catalog cross-reference; comparable types are not guaranteed identical
Minimum Operating Supply Voltage	170 V	Published for comparable RFT type Z560M
Cathode Current Minimum	1 mA	Published for comparable RFT type Z560M
Cathode Current Maximum	2.5 mA	Published for comparable RFT type Z560M
Peak Cathode Current	10 mA	Published for comparable RFT type Z560M
Ambient Temperature Minimum	-50 °C	Published for comparable RFT type Z560M
Ambient Temperature Maximum	70 °C	Published for comparable RFT type Z560M
Displayed Symbols	0 to 9	Published for comparable RFT type Z560M
Reading Direction	front	Published for comparable RFT type Z560M
Symbol Height	15.5 mm	Published for comparable RFT type Z560M
Maximum Viewing Distance	10 m	Published for comparable RFT type Z560M
Mounting Orientation	Pin 8 uppermost	Published for comparable RFT type Z560M
Maximum Bulb Height	26.5 mm	Published for comparable RFT type Z560M
Maximum Bulb Diameter	30.1 mm	Published for comparable RFT type Z560M

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Anode Striking Voltage	145 V	Published for comparable RFT type Z560M
Anode Maintaining Voltage	135 V	Published for comparable RFT type Z560M
Anode Extinction Voltage	120 V	Published for comparable RFT type Z560M

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker