

ELECTRONIC TUBE REFERENCE

LG76

Specialized - Switching Tube electronic tube

CONSOLIDATED TECHNICAL DATA
1 SECTION
CONSTRUCTION
TRIGGERPULSESWITCH

Nullode pulse-discharge switching tube with approximately 1-2 microsecond blocking time for rapid pulse-control applications.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	— / —	PARALLEL HEATER	— / —
HEATING	Indirect; cold cathode	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 TriggerPulseSwitch	
STARTING VOLTAGE	800 V
MAINTAINING VOLTAGE	375 V
Published ratings and characteristics promoted from the approved datasheet.	

Nullode pulse-discharge tube with approximately 1-2 microsecond blocking time.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

194X Wehrmacht Rohren

Published test conditions and operating points. Values on this page are preserved as reported by this source.

194X WEHRMACHT ROHREN

Section 1 · TriggerPulseSwitch

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Blocking time minimum	1 us	Published datasheet value

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Blocking time maximum	2 us	Published datasheet value

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker