



ELECTRONIC TUBE REFERENCE

M8081

Voltage - Dual Triode (similar high frequency) electronic tube

CONSOLIDATED TECHNICAL DATA

2 SECTIONS

CONSTRUCTION

TRIODE-TRIODE

Special-quality VHF double triode for equipment exposed to severe vibration and shock, with statistically controlled characteristics and operation extending to approximately 250 MHz.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 450 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Triode	
PLATE RESISTANCE	6800 Ω
TRANSCONDUCTANCE	0.0056 S
AMPLIFICATION FACTOR	38
MAXIMUM PLATE VOLTAGE	330 V
MAXIMUM PLATE DISSIPATION	1.6 W
<i>Representative of two identical special-quality VHF triode sections.</i>	

SECTION2 Triode	
PLATE RESISTANCE	6800 Ω
TRANSCONDUCTANCE	0.0056 S
AMPLIFICATION FACTOR	38
MAXIMUM PLATE VOLTAGE	330 V
MAXIMUM PLATE DISSIPATION	1.6 W
<i>Second physical triode section; identical twin section represented explicitly.</i>	

Special-quality VHF double triode for equipment subject to vibration and shock with statistically controlled characteristics.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1963 Mullard

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1963 MULLARD

Section 1 · Triode

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater Voltage	6.3 V	—
Heater Current	450 mA	—
Plate Voltage	100 V	EachSection
Plate Current	9 mA	EachSection
Cathode Voltage	0.9 V	EachSection
Transconductance	5600 μ S	EachSection
Amplification Factor	38 ratio	EachSection
Plate Resistance	6800 ohm	EachSection
Plate-Grid Capacitance	1.6 pF	EachSection
Input Capacitance	2.1 pF	EachSection

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum Operating Frequency	250 MHz	—

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1967 Mullard Receiving Tubes for Maintenance

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1967 MULLARD RECEIVING TUBES FOR MAINTENANCE

Section 1 · Triode

CAPACITANCE		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
* C_{a-g1}	6 pF	Published in approved M8081.pdf target datasheet; Section1
* C_{i-n}	2.1 pF	Published in approved M8081.pdf target datasheet; Section1
$C_{out'}$	0.45 pF	Published in approved M8081.pdf target datasheet; Section1
$C_{out''}$	0.35 pF	Published in approved M8081.pdf target datasheet; Section1
$C_{ll-I<}$	4 pF	Published in approved M8081.pdf target datasheet; Section1
(in 1.4	2.8 pF	Published in approved M8081.pdf target datasheet; Section1
250	0.55 pF	Published in approved M8081.pdf target datasheet; Section1
($a-I\{ 1.2$	1.8 pF	Published in approved M8081.pdf target datasheet; Section1

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
I_a	9 mA	Published in approved M8081.pdf target datasheet; Section1
g_m	5.6 mA	Published in approved M8081.pdf target datasheet; Section1

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
$I_{I< max}$	25 mA	Published in approved M8081.pdf target datasheet; Section1
i. max. 2 x	4.5 mA	Published in approved M8081.pdf target datasheet; Section1
Maximum acceleration (continuous operation)	2.5 g	Published in approved M8081.pdf target datasheet; Section1
Maximum shock (short duration)	500 g	Published in approved M8081.pdf target datasheet; Section1
Heater current 0.65 420	480 mA	Published in approved M8081.pdf target datasheet; Section1
Anode current 0.65 6.5	11.5 mA	Published in approved M8081.pdf target datasheet; Section1

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Rk = 1, 5kQ , Rg • = Rg • = on. 2.5	15 mV	Published in approved M8081.pdf target datasheet; Section1
oth e r voltages appli ed ,	2 g	Published in approved M8081.pdf target datasheet; Section1
No app lied volt ages,	500 g	Published in approved M8081.pdf target datasheet; Section1

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker