



ELECTRONIC TUBE REFERENCE

N41

Power - Pentode Single (NOT beam) (under 10W) electronic tube

CONSOLIDATED TECHNICAL
DATA

1 SECTION
CONSTRUCTION
PENTODE

High-transconductance Osram power pentode for substantial receiver audio output.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	7
NOMINAL HEATER	4 V / 2 A	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Pentode	
TRANSCONDUCTANCE	0.01 S
MAXIMUM PLATE VOLTAGE	250 V
MAXIMUM SCREEN VOLTAGE	250 V
MAXIMUM PLATE DISSIPATION	8 W
<i>Published ratings and characteristics promoted from the approved datasheet.</i>	

OSRAM N41 pentode for amplification or power-output service as specified in the supplied datasheet.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1937 Osram Valves

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1937 OSRAM VALVES

Section 1 · Pentode

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Optimum load resistance	7800 ohm	Published operating data



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

193X Osram

Published test conditions and operating points. Values on this page are preserved as reported by this source.

193X OSRAM

Section 1 · Pentode

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater/Filament Voltage	4 V	Published datasheet value
Heater/Filament Current	2 A	Published datasheet value
Maximum Anode Voltage	250 V	Published datasheet value
Maximum Screen Voltage	250 V	Published datasheet value
Maximum Anode Dissipation	8 W	Published datasheet value

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Mutual Conductance	10000 μ S	Published datasheet value