

Mercury-pool ignitron power switch for industrial welding, rectifier, or high-current control service.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	— / —	PARALLEL HEATER	— / —
HEATING	Indirect; cold cathode	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 IgnitronPowerSwitch
No fixed ratings recorded.
Mercury-pool ignitron AC-control/rectifier section.

NL5550 water-cooled or industrial mercury-pool ignitron for welding/control service.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1957 National Electronics

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1957 NATIONAL ELECTRONICS

Section 1 · IgnitronPowerSwitch

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
AC control frequency minimum	25 Hz	—
AC control frequency maximum	60 Hz	—
Peak forward voltage	6000 V	CapacitorDischarge
Peak inverse voltage	3000 V	CapacitorDischarge
Peak anode current	500 A	CapacitorDischarge

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker