ELECTRONIC TUBE REFERENCE

NL842

Nixie electronic tube

CONSOLIDATED TECHNICAL DATA
1 SECTION
CONSTRUCTION
NIXIE

Long-life neon-filled cold-cathode numerical readout tube displaying digits 0–9 with decimal-point capability. Manufacturer data specify a 170 V maximum ionization voltage and minimum supply, together with operating cathode-current limits.

General characteristics

BASE DESIGNATION	—	**BASE PINS**	—
NOMINAL HEATER	— / —	**PARALLEL HEATER**	— / —
HEATING	Indirect; cold cathode	**SERIES OPERATION**	Not specified
CATHODE ARRANGEMENT	Separate cathodes	**SECTION CONSTRUCTION**	Similar

Section ratings

SECTION1 Nixie	
MAXIMUM PLATE VOLTAGE	170 V
MAXIMUM CATHODE CURRENT	3.5 mA
Cold-cathode glow display section; peak cathode-current limit promoted.	

NL842 is a long-life neon-filled cold-cathode display/readout tube displaying numerals 0–9 with decimal-point capability. The supplied sheet specifies a 170 V maximum ionization voltage, 170 V minimum supply, and published cathode-current limits.

SOURCE OPERATING CONDITIONS

1968 Nixie National Electronics

SOURCE PDF

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1968 NIXIE NATIONAL ELECTRONICS

Section 1 · Nixie

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Ionization Voltage Maximum	**170 V**	Published technical information
Peak Cathode Current Maximum	**3.5 mA**	Published technical information
Average Cathode Current Maximum	**3 mA**	Published technical information
Ambient Temperature Minimum	**-20 degC**	Normal life range
Ambient Temperature Maximum	**55 degC**	Normal life range
Decimal Point Current Maximum	**0.5 mA**	Published technical information
Recommended Supply Voltage	**170 V**	Published technical information
Recommended Supply Voltage	**250 V**	Published technical information
Recommended Supply Voltage	**300 V**	Published technical information

CHARACTERISTIC

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Supply Voltage Minimum	**170 V**	Published technical information
Average Cathode Current Minimum	**0.2 mA**	Published technical information
Prebias Voltage Minimum	**60 V**	Off cathodes
Prebias Voltage Maximum	**120 V**	Off cathodes
Dynamic Life	**200000 h**	Published dynamic life
Decimal Point Current Minimum	**0.1 mA**	Published technical information

Tube Tinker

An independent reference for electronic tubes, vacuum tubes, and their source documents.

Catalog Tube types Full books Blog Feedback & corrections

© 2026 Tube Tinker