

Russian cold-cathode Dekatron for counting, switching, and counting-calculating equipment, providing visible glow indication of the active position.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	— / —	PARALLEL HEATER	— / —
HEATING	Indirect; cold cathode	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Nixie

No fixed ratings recorded.

Electrical values not fitting canonical promoted fields are preserved in TUBE_SECTION_PARAMETER.

Russian cold-cathode glow-discharge Dekatron intended for counting, switching, or counting-and-calculating equipment. It transfers a visible discharge among cathodes; glow indication is used for indication.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

196X Nixie Russian 1

Published test conditions and operating points. Values on this page are preserved as reported by this source.

196X NIXIE RUSSIAN 1

Section 1 · Nixie

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Scale factor	30	Published datasheet value
Supply voltage	450 V	Published datasheet value
Discharge starting voltage	—375 V	Published datasheet value
Discharge maintaining voltage	280 V	Published datasheet value
Subcathode bias voltage	36–44 V	Published datasheet value
Reset pulse amplitude	135–165 V	Published datasheet value
Operating current	0.3–0.4 mA	Published datasheet value
Counting rate	0.001–2000 Hz	Published datasheet value
Control pulse amplitude	120–170 V	Published datasheet value
Control pulse duration	150–170 us	Published datasheet value
Control pulse rise time	10–90 us	Published datasheet value
Service life	1000— h	Published datasheet value