



ELECTRONIC TUBE REFERENCE

PEN24

Power - Pentode (NOT beam) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
PENTODE

Power/output pentode designed for audio-frequency output amplification in receiver or push-pull amplifier service.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	8
NOMINAL HEATER	2 V / 300 mA	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Pentode	
TRANSCONDUCTANCE	0.0057 S
MAXIMUM PLATE VOLTAGE	150 V
MAXIMUM SCREEN VOLTAGE	150 V

High-sensitivity battery output pentode for portable receivers.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1960 Mazda

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1960 MAZDA

Section 1 · Pentode

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Typical Plate Voltage	120 V	—
Typical Screen Voltage	120 V	—
Typical Plate Current	5 mA	—
Power Output	0.44 W	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker