



ELECTRONIC TUBE REFERENCE

PTT208P

Power - Pentode Single (NOT beam) (under 10W) electronic tube

CONSOLIDATED TECHNICAL
DATA

1 SECTION
CONSTRUCTION
PENTODE

Long-life power pentode for professional low-frequency output stages, co-designated with R147.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	18 V / 140 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Pentode	
PLATE RESISTANCE	140000 Ω
TRANSCONDUCTANCE	0.006 S
MAXIMUM PLATE VOLTAGE	225 V
MAXIMUM SCREEN VOLTAGE	225 V
MAXIMUM PLATE DISSIPATION	4 W
MAXIMUM SCREEN DISSIPATION	0.8 W
<i>Published ratings and characteristics promoted from the approved source.</i>	

Long-life power-amplifier pentode for low-frequency output stages.

SOURCE OPERATING CONDITIONS

1953 La Radiotechnique

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1953 LA RADIOTECHNIQUE

Section 1 · Pentode

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
HeaterVoltageNominal	18 V	Nominal
HeaterCurrentNominal	140 mA	Nominal
Maximum Plate Voltage	225 V	—
Maximum Screen Voltage	225 V	—
Maximum Plate Dissipation	4 W	—
Maximum Screen Dissipation	0.8 W	—

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Transconductance	6000 μ S	Typical
Amplification Factor	840	Typical
Plate Resistance	140000 ohm	Typical