



ELECTRONIC TUBE REFERENCE

PTT213P

Voltage - Pentode High Frequency (single) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

PENTODE

Long-life professional pentode designed for voltage amplification, with high-frequency or wideband service where specified by the manufacturer.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 300 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Pentode	
PLATE RESISTANCE	500000 Ω
TRANSCONDUCTANCE	0.0085 S
MAXIMUM PLATE VOLTAGE	225 V
MAXIMUM SCREEN VOLTAGE	225 V
MAXIMUM PLATE DISSIPATION	2.6 W
MAXIMUM SCREEN DISSIPATION	0.6 W
Published ratings and characteristics promoted from the approved source.	

Long-life high-transconductance voltage-amplifier pentode for high-frequency service.

SOURCE OPERATING CONDITIONS

1953 La Radiotechnique

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1953 LA RADIOTECHNIQUE

Section 1 · Pentode

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
HeaterVoltageNominal	6.3 V	Nominal
HeaterCurrentNominal	300 mA	Nominal
Maximum Plate Voltage	225 V	—
Maximum Screen Voltage	225 V	—
Maximum Plate Dissipation	2.6 W	—
Maximum Screen Dissipation	0.6 W	—

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Transconductance	8500 μ S	Typical
Amplification Factor	4250	Typical
Plate Resistance	500000 ohm	Typical

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker