

ELECTRONIC TUBE REFERENCE

QK338

Specialized - Magnetron electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
MAGNETRON

Fixed-frequency high-power pulsed magnetron designed for radar and related short-pulse microwave service in its specified operating band.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	8.3 V / 85 A	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Magnetron	
MAXIMUM PLATE VOLTAGE	76000 V
MAXIMUM CATHODE CURRENT	135 A
Published ratings and characteristics promoted where clearly stated; identical repeated sections compressed where applicable.	

Printed co-designation for the RK6410 fixed-frequency 5 MW pulsed magnetron.



SOURCE OPERATING CONDITIONS

1938 Raytheon

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1938 RAYTHEON

Section 1 · Magnetron

CHARACTERISTICS

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater or filament voltage	8.3 V	Published nominal or representative value
Heater or filament current	85 A	Published nominal or representative value
Frequency range	2750–2860 MHz	Published operating or tuning range

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
RF power output	5000000 W	Published nominal or minimum output
Maximum pulse duration	2.2 us	Published pulse limit
Maximum duty cycle	0.001 fraction	Published duty-cycle limit

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker