



ELECTRONIC TUBE REFERENCE

RD24GA

Diode (NOT rectifier) electronic tube

CONSOLIDATED TECHNICAL DATA

2 SECTIONS

CONSTRUCTION

DIODE-DIODE

German dual diode with published high-frequency operating data, intended for specialized RF detector and rectifier applications.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	— / 60 mA	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Common cathode	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Diode	
MAXIMUM PLATE VOLTAGE	50 V
MAXIMUM CATHODE CURRENT	0.2 mA
PEAK INVERSE VOLTAGE	50 V
NOMINAL OUTPUT CURRENT	0.2 mA
PEAK FORWARD CURRENT	2 mA
<i>Published ratings and characteristics promoted; additional useful values retained as parameters.</i>	

SECTION2 Diode	
<i>No fixed ratings recorded.</i>	
<i>Physical diode section added during approved section-structure reconciliation.</i>	

RD24GA: German dual diode with published electrical ratings and operating data. The German-language datasheet was translated and interpreted by technical meaning, with ratings and characteristics

preserved.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

194X Wehrmacht Rohren

Published test conditions and operating points. Values on this page are preserved as reported by this source.

194X WEHRMACHT ROHREN

Section 1 · Diode

CHARACTERISTICS

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater current	60 mA	—

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum anode voltage	50 V	—
Maximum cathode/anode current	0.2 mA	—
Maximum peak anode voltage	50 V	PerSection
Maximum DC anode current	0.2 mA	PerSection
Maximum peak anode current	2 mA	PerSection

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker