

ELECTRONIC TUBE REFERENCE

RE064

Voltage - Triode (single) electronic tube

CONSOLIDATED TECHNICAL DATA
1 SECTION
CONSTRUCTION
TRIODE

Early directly heated Telefunken receiving triode for voltage amplification and receiver front-end service.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	4 V / 60 mA	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Triode	
PLATE RESISTANCE	22200 Ω
TRANSCONDUCTANCE	0.00045 S
AMPLIFICATION FACTOR	10
MAXIMUM PLATE VOLTAGE	100 V
Early-stage amplifier triode.	

The Telefunken RE064 is a directly heated early receiving triode used for voltage amplification or receiver front-end service.

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker