

ELECTRONIC TUBE REFERENCE

REN914

Voltage - Triode (single) electronic tube

CONSOLIDATED TECHNICAL DATA
1 SECTION
CONSTRUCTION
TRIODE

High-gain input triode for detector and resistance-coupled audio amplification.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	4 V / 1 A	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Triode	
MAXIMUM PLATE VOLTAGE	200 V
Published historical Telefunken data promoted where legible; surrounding handbook text used only for the filename-designated tube.	

High-gain input triode for detector and resistance-coupled audio amplification.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1959 Telefunken

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1959 TELEFUNKEN

Section 1 · Triode

APPLICATION		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Application	High-gain detector / AF input stage	—