

ELECTRONIC TUBE REFERENCE

RENS1234

Voltage Pentode - Sharp Cutoff (single) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

PENTODE

High-frequency receiving pentode designed for RF and intermediate-frequency amplifier service.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	4 V / 1 A	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Pentode	
MAXIMUM PLATE VOLTAGE	250 V
MAXIMUM SCREEN VOLTAGE	100 V
Published historical Telefunken data promoted where legible; surrounding handbook text used only for the filename-designated tube.	

RF/IF pentode for receiver amplification.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1959 Telefunken

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1959 TELEFUNKEN

Section 1 · Pentode

APPLICATION		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Application	RF / IF amplifier	—