ELECTRONIC TUBE REFERENCE

RENS1374

Voltage - Pentode Sharp Cutoff (single) electronic tube

CONSOLIDATED TECHNICAL DATA
1 SECTION
CONSTRUCTION
PENTODE

High-frequency receiving pentode designed for RF and intermediate-frequency amplifier service.

General characteristics

BASE DESIGNATION	–	**BASE PINS**	–
NOMINAL HEATER	4 V / 1 A	**PARALLEL HEATER**	– / –
HEATING	Indirect	**SERIES OPERATION**	Not specified
CATHODE ARRANGEMENT	Separate cathodes	**SECTION CONSTRUCTION**	Similar

Section ratings

SECTION1 Pentode	
MAXIMUM PLATE VOLTAGE	250 V
MAXIMUM SCREEN VOLTAGE	100 V
Published historical Telefunken data promoted where legible; surrounding handbook text used only for the filename-designated tube.	

High-frequency pentode for RF/IF amplifier service.

SOURCE OPERATING CONDITIONS

1959 Telefunken

SOURCE PDF

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1959 TELEFUNKEN

Section 1 · Pentode

APPLICATION		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Application	**RF / IF amplifier**	—

Tube Tinker

An independent reference for electronic tubes, vacuum tubes, and their source documents.

Catalog Tube types Full books Blog Feedback & corrections

© 2026 Tube Tinker