

ELECTRONIC TUBE REFERENCE

RENS1819

Voltage Pentode - Remote Cutoff (single) electronic tube

CONSOLIDATED TECHNICAL DATA
1 SECTION
CONSTRUCTION
PENTODE

Telefunken remote-cutoff RF/IF pentode for 180 mA series-heater receivers and fading-compensation service.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	4 V / 180 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Pentode	
MAXIMUM PLATE VOLTAGE	200 V
MAXIMUM SCREEN VOLTAGE	100 V
Published historical Telefunken data promoted where legible; filename-designated tube kept distinct from surrounding handbook entries.	

Variable-control RF/IF pentode for 180 mA series-heater receivers; fading-compensation service.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1959 Telefunken

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1959 TELEFUNKEN

Section 1 · Pentode

CHARACTERISTICS

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Cutoff characteristic	Variable-control / exponential	—

APPLICATION

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Application	RF / IF amplifier with fading control	—