



ELECTRONIC TUBE REFERENCE

RH6C

Power - Triode electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TRIODE

Siemens metal-ceramic disc-seal power triode for microwave oscillator and amplifier service to about 7 GHz. Its compact low-inductance construction and high transconductance suit microwave cavities and frequency-conversion applications.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6 V / —	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Triode	
TRANSCONDUCTANCE	0.016 S
AMPLIFICATION FACTOR	60
MAXIMUM PLATE VOLTAGE	600 V
MAXIMUM PLATE DISSIPATION	25 W
MAXIMUM GRID DISSIPATION	0.15 W

Air-cooled disc-seal triode in metal-ceramic construction for oscillators, frequency multipliers and amplifiers to about 7 GHz; supplied with an anode radiator.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1963 Siemens

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1963 SIEMENS

Section 1 · Triode

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Frequency range	7 GHz	Amplifier/Oscillator

CAPACITANCE

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Grid-cathode capacitance	2.6 pF	—
Plate-grid capacitance	1.7 pF	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker