



ELECTRONIC TUBE REFERENCE

RL24T1

Power - Triode electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TRIODE

German directly heated transmitting triode with published limiting ratings and operating data.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	24 V / 165 mA	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Triode	
TRANSCONDUCTANCE	0.0024 S
MAXIMUM PLATE DISSIPATION	15 W
<i>Published ratings and characteristic constants promoted where reliably identified; other useful data retained as parameters.</i>	

RL24T1: German transmitting triode with published limiting ratings and operating data. The complete German-language datasheet was interpreted by technical meaning, including ratings, characteristics and operating conditions.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

194X Wehrmacht Rohren

Published test conditions and operating points. Values on this page are preserved as reported by this source.

194X WEHRMACHT ROHREN

Section 1 · Triode

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater voltage	24 V	—
Heater current	165 mA	—
Transconductance	2400 μ S	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum anode dissipation	15 W	—