



ELECTRONIC TUBE REFERENCE

RL2T2

Power - Triode electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TRIODE

German directly heated transmitting triode with published limiting ratings and operating data.

GENERAL CHARACTERISTICS

BASE DESIGNATION	–	BASE PINS	–
NOMINAL HEATER	19 V / –	PARALLEL HEATER	– / –
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Triode	
TRANSCONDUCTANCE	0.00183 S
AMPLIFICATION FACTOR	105
MAXIMUM PLATE VOLTAGE	150 V
MAXIMUM PLATE DISSIPATION	2 W
<i>Published ratings and characteristic constants promoted where reliably identified; other useful data retained as parameters.</i>	

RL2T2: German transmitting triode with published limiting ratings and operating data. The complete German-language datasheet was interpreted by technical meaning, including ratings, characteristics and operating conditions.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

194X Wehrmacht Rohren

Published test conditions and operating points. Values on this page are preserved as reported by this source.

194X WEHRMACHT ROHREN

Section 1 · Triode

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater voltage	19 V	—
Transconductance	1830 μ S	—
Amplification factor	105	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum anode voltage	150 V	—
Maximum anode dissipation	2 W	—