



ELECTRONIC TUBE REFERENCE

RS2064CL

Power - Tetrode (NOT beam) (over 1000V 100W) electronic tube

CONSOLIDATED TECHNICAL
DATA

1 SECTION
CONSTRUCTION
TETRODE

High-power transmitting tetrode designed primarily for broadcast, FM, VHF, medium-wave, or short-wave transmitter RF power service.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	9 V / 112 A	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Tetrode	
TRANSCONDUCTANCE	0.08 S
MAXIMUM PLATE VOLTAGE	12000 V
MAXIMUM SCREEN VOLTAGE	1000 V
MAXIMUM PLATE DISSIPATION	10000 W
MAXIMUM SCREEN DISSIPATION	270 W
MAXIMUM GRID DISSIPATION	70 W

Coaxial metal-ceramic tetrode, forced-air-cooled, particularly suitable for FM transmitters in grounded control-grid/screen-grid circuits to 110 MHz.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1963 Siemens

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1963 SIEMENS

Section 1 · Tetrode

CHARACTERISTICS

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Transconductance	80 mA/V	—

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum anode voltage	12 kV	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker