

ELECTRONIC TUBE REFERENCE

S1330DV

Specialized - Ignitron electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

IGNITRONPOWERSWITCH

Heavy-current thyatron for industrial controlled-power service. Its massive directly heated cathode supports substantial gas-discharge current.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	2.5 V / 9 A	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 IgnitronPowerSwitch	
MAXIMUM PLATE VOLTAGE	1300 V
Published electrical limits and characteristics promoted from the approved source.	

Noble-gas thyatron with directly heated oxide cathode and control grid for electronic control systems, stepless motor-speed control and ignitron triggering.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1953 RFT Rundfunk Technik

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1953 RFT RUNDFUNK TECHNIK

Section 1 · IgnitronPowerSwitch

CHARACTERISTICS

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater or filament voltage	2.5 V	Published nominal value
Heater or filament current	9 A	Published nominal value

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Peak cathode current	30 A	Published peak limit

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker