

ELECTRONIC TUBE REFERENCE

SC3122

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
CATHODERAY

Electrostatically focused, magnetically deflected monitor CRT with a flat P4 faceplate. Sylvania specifies high-voltage operation to approximately 22 kV for bright professional monitoring.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 600 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	22000 V
Special-purpose cathode-ray tube; published ratings and construction data captured.	

Electrostatically focused, magnetically deflected monitor CRT with flat P4 faceplate.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1950 Sylvania

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1950 SYLVANIA

Section 1 · Cathode Ray

CHARACTERISTICS

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Focusing method	Electrostatic	—
Deflection method	Magnetic	—

APPLICATION

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Application	Electrostatic charge printing	—



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1965 Sylvania Electronic Tubes Vol3

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1965 SYLVANIA ELECTRONIC TUBES VOL3

Section 1 · Cathode Ray

CHARACTERISTICS

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater voltage	6.3 V	—
Heater current	600 mA	—
Focusing method	Electrostatic	—
Deflection method	Magnetic	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum principal anode/accelerator voltage	22000 V	—
Anode voltage maximum	22000 V	—
Focus-electrode voltage range	-550 to +1100 V	—
Grid2 voltage maximum	770 V	—
Heater-cathode voltage maximum	200 V	—
Typical anode voltage	20000 V	—
Typical focus-electrode voltage range	0 to +300 V	—
Grid1 circuit resistance maximum	1.5 Mohm	—

APPLICATION		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Application	Electrostatically focused, magnetically deflected monitor CRT	—

CONSTRUCTION		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Phosphor	P4	—