



ELECTRONIC TUBE REFERENCE

SC3304

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

CATHODERAY

High-voltage special-purpose CRT with magnetic focusing and magnetic deflection. Its manufacturer documentation establishes specialized electronic display service but does not identify a narrower radar, television, or oscilloscope application.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 600 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	25000 V
Special-purpose cathode-ray tube; published ratings and construction data captured.	

High-voltage special-purpose CRT with magnetic focus and magnetic deflection.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1950 Sylvania

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1950 SYLVANIA

Section 1 · Cathode Ray

CHARACTERISTICS

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Focusing method	Magnetic	—
Deflection method	Magnetic	—

APPLICATION

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Application	Electrostatic charge printing	—

CONSTRUCTION

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Fiber optics faceplate	Yes	—



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1965 Sylvania Electronic Tubes Vol3

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1965 SYLVANIA ELECTRONIC TUBES VOL3

Section 1 · Cathode Ray

CHARACTERISTICS

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater voltage	6.3 V	—
Heater current	600 mA	—
Focusing method	Magnetic	—

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Deflection method	Magnetic	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum principal anode/accelerator voltage	25000 V	—
Anode voltage maximum	25000 V	—
Grid2 voltage maximum	2500 V	—
Typical anode voltage	20000 V	—
Typical grid2 voltage	2000 V	—
Grid1 circuit resistance maximum	1.5 Mohm	—

APPLICATION		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Application	High-voltage special-purpose CRT	—