



ELECTRONIC TUBE REFERENCE

SP41

Voltage - Pentode High Frequency (single) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

PENTODE

Screened high-frequency pentode designed for television HF and IF amplifier stages and also usable as a video-output valve.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	8
NOMINAL HEATER	4 V / 950 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Pentode	
TRANSCONDUCTANCE	0.0085 S
MAXIMUM PLATE VOLTAGE	250 V
MAXIMUM SCREEN VOLTAGE	250 V

Screened high-frequency pentode for H.F. and I.F. stages of television receivers; also usable as a video-output valve.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1960 Mazda

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1960 MAZDA

Section 1 · Pentode

CAPACITANCE		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Anode-earth capacitance	5 pF	—
Grid-earth capacitance	10.75 pF	—
Anode-grid capacitance	0.003 pF	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker