



ELECTRONIC TUBE REFERENCE

SRS301

Power - Triode electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TRIODE

Radiation-cooled transmitting power triode for RF generators, communications, and electromedical equipment. Rated for approximately 900 W plate dissipation, providing substantial professional RF power without external liquid cooling.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	10 V / 20 A	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1	Triode
MAXIMUM PLATE DISSIPATION	900 W
Published ratings and characteristics promoted where clearly stated.	

Radiation-cooled 900-watt transmitting triode for RF generators, communications and electromedical equipment.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1953 RFT Rundfunk Technik

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1953 RFT RUNDFUNK TECHNIK

Section 1 · Triode

APPLICATION		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Application	RFPower text	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker