



ELECTRONIC TUBE REFERENCE

SRS360

Power - Triode (over 1000V 100W) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
TRIODE

Radiation-cooled directly heated transmitting triode for RF and audio amplification, modulation, and oscillator service. Rated for approximately 250 W plate dissipation, with published RF output around 750 W to about 150 MHz.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 14 A	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Triode	
TRANSCONDUCTANCE	0.0055 S
MAXIMUM PLATE VOLTAGE	3000 V
MAXIMUM PLATE DISSIPATION	250 W
MAXIMUM GRID DISSIPATION	30 W
MAXIMUM CATHODE CURRENT	480 mA
<i>Promoted ratings/characteristics are source-published values; additional published values and operating examples are preserved in the parameter table.</i>	

Radiation-cooled directly heated transmitting triode for RF and audio amplification, modulation and oscillator service.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1953 RFT Rundfunk Technik

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1953 RFT RUNDFUNK TECHNIK

Section 1 · Triode

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum Frequency	150 MHz	—
RFOutputPower	750 W	—

APPLICATION		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Application	RFPower text	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker