



ELECTRONIC TUBE REFERENCE

STR15060

Voltage Regulator electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

VOLTAGEREGULATOR

Higher-current 150 V gas regulator operating over approximately 5–60 mA for heaterless shunt stabilization with greater current capability.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	— / —	PARALLEL HEATER	— / —
HEATING	Indirect; cold cathode	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Voltage Regulator	
REGULATOR VOLTAGE	150 V
MINIMUM REGULATOR CURRENT	5 mA
MAXIMUM REGULATOR CURRENT	60 mA
STARTING VOLTAGE	180 V
MAINTAINING VOLTAGE	150 V
DYNAMIC IMPEDANCE	150 Ω
<i>Published glow-discharge voltage-stabilizer characteristics.</i>	

A cold-cathode glow-discharge voltage regulator for automatic stabilization of a 150 V DC supply up to 60 mA.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1953 RFT Rundfunk Technik

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1953 RFT RUNDFUNK TECHNIK

Section 1 · Voltage Regulator

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Nominal maintaining voltage	150 V	—
Voltage variation over current range	7.5 V	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Current range	5 to 60 mA	—
Nominal current	35 mA	—