ELECTRONIC TUBE REFERENCE

T980N

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA
1 SECTION
CONSTRUCTION
CATHODERAY

English Electric cathode-ray instrument tube with electrostatic beam control and precision deflection, intended for oscillographic or measurement display with screen characteristics designated by type T980N.

General characteristics

BASE DESIGNATION	B12F	**BASE PINS**	12
NOMINAL HEATER	6.3 V / 300 mA	**PARALLEL HEATER**	— / —
HEATING	Indirect	**SERIES OPERATION**	Not specified
CATHODE ARRANGEMENT	Separate cathodes	**SECTION CONSTRUCTION**	Similar

Section ratings

SECTION1 Cathode Ray

No fixed ratings recorded.

Maximum final-anode/PDA voltage mapped to MaxPlateVoltage.

Five-inch wide-band high-speed oscilloscope cathode-ray tube with electrostatic focus and deflection, post-deflection acceleration, and anode modulation electrodes. N screen

SOURCE OPERATING CONDITIONS

1971 English Electric Valve

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1971 ENGLISH ELECTRIC VALVE

Section 1 · Cathode Ray

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater voltage	**6.3 V**	—
Heater current	**300 mA**	—
Maximum anode 4 voltage	**3.3 kV**	—
Maximum anode 3/anode 1 voltage	**3.3 kV**	—
Maximum anode 2 voltage	**1.5 kV**	—
Typical PDA/screen voltage	**12 kV**	—

CHARACTERISTIC

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Screen characteristic	**N screen**	—

CAPACITANCE

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Grid to all other electrodes capacitance	**6.1 pF**	—

Tube Tinker

An independent reference for electronic tubes, vacuum tubes, and their source documents.

Catalog Tube types Full books Blog Feedback & corrections

© 2026 Tube Tinker