

ELECTRONIC TUBE REFERENCE

TCM13X

Specialized - Cathode Ray electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
CATHODERAY

Barrier-grid electrostatic storage tube that records electrical signals as charge patterns on a dielectric target. Its storage structure retains information for subsequent viewing or electronic readout.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 600 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Cathode Ray	
MAXIMUM PLATE VOLTAGE	1500 V
MAXIMUM CATHODE CURRENT	1 mA
Published source values promoted where applicable; additional electrical, storage, RF, pulse and cooling data retained as parameters.	

Barrier-grid electrostatic storage tube for storing electrical signals as charge patterns on a dielectric target.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1958 Compagnie General

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1958 COMPAGNIE GENERAL

Section 1 · Cathode Ray

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Storage method	Barrier-grid electrostatic storage	—
Focusing method	Electrostatic	—
Deflection method	Electrostatic	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker