

ELECTRONIC TUBE REFERENCE

TH364

Power - Triode (over 1000V 100W) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
TRIODE

Forced-air-cooled ceramic-metal planar triode for oscillator, amplifier, and frequency-multiplier service through approximately 3 GHz.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 1.3 A	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Triode	
MAXIMUM PLATE VOLTAGE	10000 V
MAXIMUM PLATE DISSIPATION	100 W
MAXIMUM GRID DISSIPATION	1.5 W
MAXIMUM CATHODE CURRENT	150 mA

Forced-air-cooled ceramic-metal planar triode for oscillator, amplifier and multiplier service to 3 GHz.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1972 Thomson CSF

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1972 THOMSON CSF

Section 1 · Triode

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Operating Frequency	3000 MHz	—
Maximum Anode Voltage	10000 V	—
Maximum Anode Dissipation	100 W	—
Maximum Grid Dissipation	1.5 W	—
Maximum/Peak Cathode Current	150 mA	—
Peak Anode Voltage	10000 V	Pulse modulator
Pulse Duration	6 us	—
Duty Factor	0.0033	—

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater/Filament Voltage	6.3 V	—
Heater/Filament Current	1.3 A	—

CAPACITANCE		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Cathode-Grid Capacitance	8 pF	—
Grid-Anode Capacitance	1.8 pF	—
Cathode-Anode Capacitance	0.06 pF	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker