

ELECTRONIC TUBE REFERENCE

U14

Rectifier - Full Wave electronic tube

CONSOLIDATED TECHNICAL DATA
2 SECTIONS
CONSTRUCTION
RECTIFIER-RECTIFIER

Directly heated full-wave rectifier with dual electrode system for higher-voltage AC mains supplies, providing approximately 120 mA DC output with greater inverse-voltage capability than U12.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	4
NOMINAL HEATER	4 V / 2.5 A	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Common cathode	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Rectifier	
PEAK INVERSE VOLTAGE	1500 V
NOMINAL OUTPUT CURRENT	120 mA
MAXIMUM HEATER-CATHODE VOLTAGE	0 V
Published ratings/characteristics promoted from the approved datasheet where legible.	

SECTION2 Rectifier	
PEAK INVERSE VOLTAGE	1500 V
NOMINAL OUTPUT CURRENT	120 mA
MAXIMUM HEATER-CATHODE VOLTAGE	0 V
Physical rectifier section 2; identical section values duplicated per physical-section policy.	

Full-wave rectifying valve with a dual electrode system for A.C. mains supplies, designed for long life and constant emission at rated filament voltage.



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

192X Marconi Valve

Published test conditions and operating points. Values on this page are preserved as reported by this source.

192X MARCONI VALVE

Section 1 · Rectifier

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
DC output voltage	500 V	Published approximate operating data



SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1937 Osram Valves

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1937 OSRAM VALVES

Section 1 · Rectifier

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater Voltage	4 V	Published datasheet value
Heater Current	2.5 A	Published datasheet value
Anode Voltage RMS	500 V	EachAnode
Rectified DC Current	120 mA	Published datasheet value
DC Output Voltage	540 V	At maximum rated AC input



1955 Marconi

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1955 MARCONI

Section 1 · Rectifier

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater/filament voltage	4 V	—
Peak inverse voltage	1500 V	—
Nominal/maximum output current	120 mA	—

CONSTRUCTION		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Rectifier topology	Bi-phase/full-wave	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes, and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)