



ELECTRONIC TUBE REFERENCE

UU4

Rectifier - Full Wave electronic tube

CONSOLIDATED TECHNICAL DATA

2 SECTIONS

CONSTRUCTION

RECTIFIER-RECTIFIER

Indirectly heated full-wave rectifying valve for AC-mains electronic equipment, providing conventional dual-section rectification for receiver, amplifier, and general DC supplies.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	4 V / 2.2 A	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Rectifier	
NOMINAL OUTPUT CURRENT	120 mA
SECTION2 Rectifier	
NOMINAL OUTPUT CURRENT	120 mA
<i>Second physical rectifier section; electrical properties populated from applicable published ratings.</i>	

AC-mains full-wave rectifying valve.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1960 Mazda

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1960 MAZDA

Section 1 · Rectifier

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum RMS anode voltage per anode	350 V	—

1960 MAZDA

Section 2 · Rectifier

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum RMS anode voltage per anode	350 V	—