



ELECTRONIC TUBE REFERENCE

UU5

Rectifier - Full Wave electronic tube

CONSOLIDATED TECHNICAL DATA

2 SECTIONS

CONSTRUCTION

RECTIFIER-RECTIFIER

Indirectly heated full-wave rectifier for AC-mains power supplies and companion to the UU4. Its four-volt heater-cathode construction provides moderate current for receiver, amplifier, and general electronic equipment.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	4 V / 2.3 A	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Rectifier	
NOMINAL OUTPUT CURRENT	120 mA
SECTION2 Rectifier	
NOMINAL OUTPUT CURRENT	120 mA

AC-mains full-wave rectifying valve companion type printed with UU4.

SOURCE OPERATING CONDITIONS

1960 Mazda

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1960 MAZDA

Section 1 · Rectifier

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum RMS anode voltage per anode	500 V	—

1960 MAZDA

Section 2 · Rectifier

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum RMS anode voltage per anode	500 V	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker