



ELECTRONIC TUBE REFERENCE

UU6

Rectifier - Full Wave electronic tube

CONSOLIDATED TECHNICAL DATA

2 SECTIONS

CONSTRUCTION

RECTIFIER-RECTIFIER

Indirectly heated full-wave rectifier for AC-mains-operated power supplies. Its four-volt heater-cathode construction provides moderate current for receiver, amplifier, and conventional electronic equipment.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	4 V / 1.4 A	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Rectifier	
NOMINAL OUTPUT CURRENT	120 mA

SECTION2 Rectifier	
NOMINAL OUTPUT CURRENT	120 mA

AC-mains full-wave rectifying valve.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1960 Mazda

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1960 MAZDA

Section 1 · Rectifier

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum RMS anode voltage per anode	350 V	—
Maximum reservoir capacitance	16 uF	—

1960 MAZDA

Section 2 · Rectifier

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum RMS anode voltage per anode	350 V	—
Maximum reservoir capacitance	16 uF	—