



ELECTRONIC TUBE REFERENCE

UU8

Rectifier - Full Wave electronic tube

CONSOLIDATED TECHNICAL DATA

2 SECTIONS

CONSTRUCTION

RECTIFIER-RECTIFIER

Indirectly heated high-current full-wave rectifier for substantial electronic power supplies. Its heavy four-volt heater-cathode construction provides considerably greater current than smaller UU-family rectifiers.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	4 V / 2.8 A	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Rectifier	
NOMINAL OUTPUT CURRENT	250 mA

SECTION2 Rectifier	
NOMINAL OUTPUT CURRENT	250 mA

Indirectly heated high-current full-wave rectifier.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1960 Mazda

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1960 MAZDA

Section 1 · Rectifier

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum RMS anode voltage per anode	350 V	—

1960 MAZDA

Section 2 · Rectifier

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum RMS anode voltage per anode	350 V	—