ELECTRONIC TUBE REFERENCE

V239C1K

Specialized - Klystron electronic tube

CONSOLIDATED TECHNICAL DATA
1 SECTION
CONSTRUCTION
KLYSTRON

Indirectly heated velocity-modulated microwave oscillator designed for coaxial or resonator service over its manufacturer-specified frequency range.

General characteristics

BASE DESIGNATION	—	**BASE PINS**	—
NOMINAL HEATER	6.3 V / 260 mA	**PARALLEL HEATER**	— / —
HEATING	Indirect	**SERIES OPERATION**	Not specified
CATHODE ARRANGEMENT	Separate cathodes	**SECTION CONSTRUCTION**	Similar

Section ratings

SECTION1 Klystron

No fixed ratings recorded.

Special-valve ratings and characteristics retained as parameters where applicable.

V239C1K is an indirectly heated velocity-modulated microwave oscillator for coaxial/resonator service. Published operating range is 3780-4040 Mc/s.

SOURCE OPERATING CONDITIONS

1946 Standard Telephone and Cables

SOURCE PDF

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1946 STANDARD TELEPHONE AND CABLES

Section 1 · Klystron

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Operating frequency range	**3780–4040 MHz**	Published operating frequency range

Tube Tinker

An independent reference for electronic tubes, vacuum tubes, and their source documents.

Catalog Tube types Full books Blog Feedback & corrections

© 2026 Tube Tinker