



ELECTRONIC TUBE REFERENCE

VP4B

Voltage - Pentode Remote Cutoff (single) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION
CONSTRUCTION
PENTODE

Variable-mu or remote-cutoff pentode designed for RF, IF, broadband, or AVC-controlled receiver amplification.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	7
NOMINAL HEATER	4 V / 650 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Pentode

No fixed ratings recorded.

Published valve ratings and characteristics promoted where applicable; additional data retained as parameters.

Variable-mu HF pentode for AC mains receiver RF amplification.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1958 Mullard Receiving Tubes

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1958 MULLARD RECEIVING TUBES

Section 1 · Pentode

APPLICATION		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Application	RF amplifier	—

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Cutoff characteristic	Variable-mu	—