



ELECTRONIC TUBE REFERENCE

W17

Voltage Pentode - Remote Cutoff (single) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

PENTODE

Battery-operated variable-mu high-frequency pentode designed for receiver RF and intermediate-frequency amplification.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	7
NOMINAL HEATER	1.4 V / 50 mA	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Pentode	
PLATE RESISTANCE	500000 Ω
TRANSCONDUCTANCE	0.0025 S
MAXIMUM PLATE VOLTAGE	250 V
MAXIMUM SCREEN VOLTAGE	250 V
MAXIMUM PLATE DISSIPATION	2.5 W
MAXIMUM SCREEN DISSIPATION	0.5 W

Miniature directly heated variable-mu RF pentode for battery receivers.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1955 Marconi

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1955 MARCONI

Section 1 · Pentode

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Heater/Filament Voltage	1.4 V	—
Transconductance	2500 μ S	—
Plate Resistance	500000 ohm	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum/Published Anode Voltage	250 V	—
Maximum/Published Screen Voltage	250 V	—
Maximum Anode Dissipation	2.5 W	—
Maximum Screen Dissipation	0.5 W	—

CAPACITANCE		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Grid-Anode Capacitance	0.006 pF	—
Input Capacitance	4.2 pF	—
Output Capacitance	7 pF	—