



ELECTRONIC TUBE REFERENCE

W30

Voltage - Pentode High Frequency (single) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

PENTODE

Universal indirectly heated high-frequency pentode from Osram. Its manufacturer description identifies broad HF signal-amplifier service rather than a narrowly specialized power, detector, or control application.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	7
NOMINAL HEATER	13 V / 300 mA	PARALLEL HEATER	— / —
HEATING	Indirect	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Pentode	
TRANSCONDUCTANCE	0.0027 S
MAXIMUM PLATE VOLTAGE	250 V
MAXIMUM SCREEN VOLTAGE	100 V
Published ratings and characteristics promoted from the approved datasheet.	

Universal indirectly heated H.F. pentode.

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker