



ELECTRONIC TUBE REFERENCE

YD1154

Power - Triode (over 1000V 100W) electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

TRIODE

Forced-air-cooled metal-ceramic RF power triode for industrial Class C oscillator service. Rated for approximately 800 W plate dissipation and 7 kV plate voltage, with moderate gain for continuous industrial RF generation.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	6.3 V / 33 A	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Triode	
PLATE RESISTANCE	4400 Ω
TRANSCONDUCTANCE	0.005 S
AMPLIFICATION FACTOR	22
MAXIMUM PLATE VOLTAGE	7000 V
MAXIMUM PLATE DISSIPATION	800 W
MAXIMUM CATHODE CURRENT	750 mA
High-power RF triode; published principal characteristic and limiting values promoted.	

Forced-air-cooled metal-ceramic RF power triode for industrial oscillator service. Published filament, capacitance, limiting-rating, and representative Class-C industrial oscillator data were extracted from the supplied Philips sheet.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1999 Philips E-Z

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1999 PHILIPS E-Z

Section 1 · Triode

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Filament voltage	6.3 V	—
Filament current	33 A	—
Transconductance	5000 μ S	—
Amplification factor	22	—

CAPACITANCE		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Anode to filament capacitance	0.3 pF	—
Grid to filament capacitance	17 pF	—
Anode to grid capacitance	11.3 pF	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum anode voltage	7000 V	—
Maximum anode current	750 mA	—
Maximum anode dissipation	800 W	—
Operating frequency	27.12 MHz	IndustrialClassC
Operating anode voltage	5000 V	IndustrialClassC;Frequency=27.12MHz
Operating anode current	550 mA	IndustrialClassC;Frequency=27.12MHz
Anode output power	2100 W	IndustrialClassC;Frequency=27.12MHz

CONSTRUCTION		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Cooling system	ForcedAir	—

TUBE TINKER

An independent reference for electronic tubes, vacuum tubes,
and their source documents.

[Catalog](#) [Tube types](#) [Full books](#) [Blog](#) [Feedback & corrections](#)

© 2026 Tube Tinker