

ELECTRONIC TUBE REFERENCE

YD1203

Power - Triode electronic tube

CONSOLIDATED TECHNICAL DATA
1 SECTION
CONSTRUCTION
TRIODE

Vapor-cooled high-power RF industrial triode designed for Class C oscillator service.

GENERAL CHARACTERISTICS

BASE DESIGNATION	—	BASE PINS	—
NOMINAL HEATER	12.2 V / 255 A	PARALLEL HEATER	— / —
HEATING	Direct	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION1 Triode	
PLATE RESISTANCE	200 Ω
TRANSCONDUCTANCE	0.15 S
AMPLIFICATION FACTOR	30
MAXIMUM PLATE VOLTAGE	14400 V
MAXIMUM PLATE DISSIPATION	80000 W
MAXIMUM CATHODE CURRENT	18 A
High-power RF triode; published principal characteristic and limiting values promoted.	

Vapour-cooled high-power RF industrial triode. Published filament, capacitance, limiting-rating, and representative Class-C industrial oscillator data were extracted from the supplied Philips sheet.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1999 Philips E-Z

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1999 PHILIPS E-Z

Section 1 · Triode

CHARACTERISTICS		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Filament voltage	12.2 V	—
Filament current	255 A	—
Transconductance	150000 μ S	—
Amplification factor	30	—

CAPACITANCE		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Anode to filament capacitance	2.7 pF	—
Grid to filament capacitance	170 pF	—
Anode to grid capacitance	55 pF	—

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Maximum anode voltage	14400 V	—
Maximum anode current	18 A	—
Maximum anode dissipation	80000 W	—
Operating frequency	30 MHz	IndustrialClassC
Operating anode voltage	12000 V	IndustrialClassC;Frequency=30MHz
Operating anode current	13 A	IndustrialClassC;Frequency=30MHz
Anode output power	123500 W	IndustrialClassC;Frequency=30MHz
Frequency for full ratings	100 MHz	—

CONSTRUCTION		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Cooling system	Vapour	—