ELECTRONIC TUBE REFERENCE

Z570M

Nixie electronic tube

CONSOLIDATED TECHNICAL DATA
1 SECTION
CONSTRUCTION
NIXIE

Gas-filled cold-cathode Nixie numerical indicator designed for decimal readout by selective glow discharge of shaped numeral cathodes.

General characteristics

BASE DESIGNATION	wire-leaded	**BASE PINS**	—
NOMINAL HEATER	— / —	**PARALLEL HEATER**	— / —
HEATING	Indirect; cold cathode	**SERIES OPERATION**	Not specified
CATHODE ARRANGEMENT	Separate cathodes	**SECTION CONSTRUCTION**	Similar

Section ratings

SECTION1 Nixie	
MAXIMUM CATHODE CURRENT	2.5 mA

Published ratings and characteristics promoted where clearly stated.

Z570M is a cold-cathode Nixie numerical/symbol indicator tube. The supplied RFT sheet gives 150 V ignition and 140 V burning voltage, a 170 V minimum operating supply, 1.5–2.5 mA cathode current, and 13 mm side-viewed symbols. Z570M is tabulated directly in the supplied RFT display-tube data sheet.

SOURCE OPERATING CONDITIONS

1953 RFT Rundfunk Technik

SOURCE PDF

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1953 RFT RUNDFUNK TECHNIK

Section 1 · Nixie

CHARACTERISTICS

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Ignition voltage	150 V	Published ignition value
Burning voltage	140 V	Published glow-discharge value

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Cathode current	2 mA	Published operating value

SOURCE DATA APPENDIX

SOURCE OPERATING CONDITIONS

1971 Nixie RFT

SOURCE PDF

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1971 NIXIE RFT

Section 1 · Nixie

CHARACTERISTIC

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Anode Ignition Voltage	150 V	Published RFT table
Anode Burning Voltage	140 V	Published RFT table
Anode Extinction Voltage	120 V	Published RFT table

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Minimum Operating Voltage	170 V	Published RFT table

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Minimum Cathode Current	**1.5 mA**	Published RFT table
Maximum Cathode Current	**2.5 mA**	Published RFT table
Peak Cathode Current	**12 mA**	Published RFT table
Minimum Ambient Temperature	**-50 degC**	Published RFT table
Maximum Ambient Temperature	**70 degC**	Published RFT table
Symbol Height	**13 mm**	Published RFT table
Maximum Viewing Distance	**8 m**	Published RFT table
Maximum Bulb Height	**47.6 mm**	Published RFT table
Maximum Bulb Diameter	**19 mm**	Published RFT table

Tube Tinker

An independent reference for electronic tubes, vacuum tubes, and their source documents.

Catalog Tube types Full books Blog Feedback & corrections

© 2026 Tube Tinker