



ELECTRONIC TUBE REFERENCE

Z5800M

Nixie electronic tube

CONSOLIDATED TECHNICAL DATA

1 SECTION

CONSTRUCTION

NIXIE

Gas-filled cold-cathode Nixie numerical indicator designed for decimal readout by selective glow discharge of shaped numeral cathodes.

GENERAL CHARACTERISTICS

BASE DESIGNATION	wire-leaded	BASE PINS	—
NOMINAL HEATER	— / —	PARALLEL HEATER	— / —
HEATING	Indirect; cold cathode	SERIES OPERATION	Not specified
CATHODE ARRANGEMENT	Separate cathodes	SECTION CONSTRUCTION	Similar

SECTION RATINGS

SECTION 1 Nixie	
MAXIMUM PLATE VOLTAGE	170 V
MAXIMUM CATHODE CURRENT	2.5 mA
STARTING VOLTAGE	150 V
MAINTAINING VOLTAGE	140 V
Cold-cathode glow-display section; maximum cathode current promoted in amperes.	

Z5800M is a cold-cathode Nixie numerical/symbol indicator tube. The supplied RFT sheet gives 150 V ignition and 140 V burning voltage, a 170 V minimum operating supply, 1.5–2.5 mA cathode current, and 13 mm side-viewed symbols. Z5800M is tabulated directly in the supplied RFT display-tube data sheet.

SOURCE OPERATING CONDITIONS

[SOURCE PDF](#)

1971 Nixie RFT

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1971 NIXIE RFT

Section 1 · Nixie

CHARACTERISTIC		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Anode Ignition Voltage	150 V	Published RFT table
Anode Burning Voltage	140 V	Published RFT table
Anode Extinction Voltage	120 V	Published RFT table

OTHER		
PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
Minimum Operating Voltage	170 V	Published RFT table
Minimum Cathode Current	1.5 mA	Published RFT table
Maximum Cathode Current	2.5 mA	Published RFT table
Peak Cathode Current	8 mA	Published RFT table
Minimum Ambient Temperature	-50 degC	Published RFT table
Maximum Ambient Temperature	70 degC	Published RFT table
Symbol Height	13 mm	Published RFT table
Maximum Viewing Distance	8 m	Published RFT table
Maximum Bulb Height	47.6 mm	Published RFT table
Maximum Bulb Diameter	19 mm	Published RFT table