ELECTRONIC TUBE REFERENCE

ZM3307

Specialized - Traveling Wave electronic tube

CONSOLIDATED TECHNICAL DATA
1 SECTION
CONSTRUCTION
TRAVELINGWAVE

Low-noise X-band traveling-wave amplifier with integral power supply for broadband microwave receiver service.

General characteristics

BASE DESIGNATION	_	**BASE PINS**	_
NOMINAL HEATER	_ / _	**PARALLEL HEATER**	_ / _
HEATING	Indirect	**SERIES OPERATION**	Not specified
CATHODE ARRANGEMENT	Separate cathodes	**SECTION CONSTRUCTION**	Similar

Section ratings

SECTION1 TravelingWave

No fixed ratings recorded.

RF performance values are retained in TUBE_SECTION_PARAMETER from the supplied GE traveling-wave-tube family sheet.

Low-noise X-band traveling-wave tube with integral power supply. The supplied General Electric data specifies a 7–11 GHz operating range, minimum small-signal gain of 25 dB, and minimum saturated output of 0.005 W.

SOURCE OPERATING CONDITIONS

SOURCE PDF

1950 General Electric Transmitting Types

Published test conditions and operating points. Values on this page are preserved as reported by this source.

1950 GENERAL ELECTRIC TRANSMITTING TYPES

Section 1 · TravelingWave

CHARACTERISTIC

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
OperatingFrequencyMinimum	**7 GHz**	—
OperatingFrequencyMaximum	**11 GHz**	—
MinimumSmallSignalGain	**25 dB**	—
MinimumSaturatedPowerOutput	**0.005 W**	—

OTHER

PARAMETER	PUBLISHED VALUE	CONDITION / NOTE
MaximumNoiseFigure	**9 dB**	—

Tube Tinker

An independent reference for electronic tubes, vacuum tubes, and their source documents.

Catalog Tube types Full books Blog Feedback & corrections

© 2026 Tube Tinker